


MONOLAYER PLANT



Surface Printing Film




General Purpose Film



Stretch Film



Shrink Film



Liner Bag

MONOLAYER PLANT



SILENT FUTURES OF WINTECH MONOLAYER PLANT

- Latest technology of Mono layer blown film line with high power efficiency, compact model with greater line speed, High production with small size & Efficient for lower thickness of film.
- Barrier Screw with water cooled Grooved Feed technology increases the output significantly.
- Extensive quality of Candle Filter increases the filtration area and provides longer life of filter to minimize down time as well as wastage level.
- Single Lip Air Ring for HMHDPE and Dule lip for LL/LD film to get optimum output capacity.

OPTIONAL FEATURES:

- Hopper loader with Dryer
- Corona Treater
- Web Aligner
- Screen Changer
- Gusset assly.
- Rotary die.

APPLICATIONS

- Surface Printing Film
- General Purpose Film
- Stretch Film
- Liner Gag
- Shrink Film

SPECIFICATIONS WINTECH MAKE MONOLAYER PLANT

Model	WTMONO-40	WTMONO-55	WTMONO-60
Screw Dia (MM)	40	55	60
L/D Ratio	30:1	30:1	30:1
Main Motor (Kw)	11	22	55
Max Output (Kg/Hr) HM	40-50	85-95	—
Max Output(Kg/Hr) - LL+LD	35-40	75-85	140-150
Film Width Rang (MM)	300-600	700-1250	1000-1500
Thickness Rang (Microns)	5-50	10-120	20-150
Die Size for HM	50-75	125 - 175	—
Die Size for LL+LD	90-100	250	325-350
Roller Size (MM)	700	1350	1600
Max Line speed	80 - 100	80	80
Surface Winder	Single Station	Two Station	Two Station