


MULTILAYER PLANT



Surface Printing Film



General Purpose Film



Lamination Film



Mulch Film



Shrink Film

MULTILAYER PLANT



SILENT FUTURES OF WINTECH MULTILAYERS

- Latest technology of IBC and Non-IBC three layer Blown Film lines with output range from 100 kg/hr to 600 kg/hr.
- Auto-Winder and Semi-Auto-Winder depend upon the application/customer demand.
- Dual Lip Air Ring with high efficiency of cooling to get optimum output with best quality.
- Bottom Supported OSC Hull-Off with latest technology and smooth rotation.
- Best wound roll geometry.
- Energy efficient screw and Grooved feed for low friction in extruder suitable for higher percentage of MLLDPE Dosing.

OPTIONAL FEATURES:

- Gravimetric system and Auto thickness control (European make) with hopper loader
- Corona Treater
- Web Aligner
- Screen Changer
- Gusset assly.
- Loadcell Control
- Auto winder in Non – IBC line

APPLICATIONS

- Surface Printing Film
- Lamination Film
- High Metallocene based Film
- General Purpose Film
- Stretch Film
- Multch Film
- Shrink Film
- Surface protection Film
- Oil Film

SPECIFICATIONS WINTECH MAKE MULTILAYER PLANT

Model	WTT 1000	WTT 1250	WTT 1500	WTT 1700	WTIBC 1250	WTIBC 1500	WTIBC 1700	WTIBC 2200	WTIBC 2500
Screw Dia (MM)	50/50/50	55/55/55	55/60/55	55/60/55	60/60/60	60/75/60	60/75/60	75/90/75	75/90/75
L/D Ratio	24:1	30:1	30:1	30:1	30:1	30:1	30:1	30:1	30:1
Main Motor (Kw)	22.5 Each	30/30/30	30/56/30	30/56/30	56/56/56	56/75/56	56/75/56	75/90/75	75/90/75
Max Output (Kg/Hr)	110-125	150-180	180-220	200-240	220-250	260-300	280-330	550-580	560-600
Film Width Rang (MM)	500-1000	700-1250	800-1500	1000-1700	700-1250	800-1500	1000-1700	1400-2200	1500-2500
Thickness Rang (Microns)	18-150	18-150	18-150	18-150	18-200	18-200	18-175	18-175	18-175
Die Size	250	300	325	350	300	325	350	550	600
Roller Size (MM)	1100	1350	1600	1800	1350	1600	1800	2300	2600
Max Line speed	60	80	80	80	120	120	120	120	120
Surface Winder	Semi Auto	Semi Auto	Semi Auto	Semi Auto	Auto	Auto	Auto	Auto	Auto